

Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 1/7

M3000000F - BCR POLY SF PARTE A

Safety Data Sheet

.1. Product identifier		
Code:	M300000F	
Product name	BCR POLY SF PARTE A	
Chemical name and synonym	Mastic based polyester resi	n unsaturated
.2. Relevant identified uses of the substar	nce or mixture and uses advised aga	inst
Intended use	Bi-component injection syst	tem for chemical anchor on construction materials
.3. Details of the supplier of the safety dat	a sheet	
Name	Bossong SpA	
Full address	via Enrico Fermi, 51	
District and Country	24050 Grassobbio	(BG)
	Italia	
	Tel. 035-3846011 Fax 035-3846012	
e-mail address of the competent person	Fax 055-5640012	
responsible for the Safety Data Sheet	tek@bossong.com	
.4. Emergency telephone number		
For urgent inquiries refer to	Ospedale NIGUARDA Milan	o tel. +39 0266101029 http://www.centroantiveleni.org/
. Hazards identification.		

The product is classified as hazardous pursuant to the provisions set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulationn 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

Eye Irrit. 2 H319 Skin Irrit. 2 H315 Skin Sens. 1 H317 Aquatic Chronic 3 H412

2.1.2. Directive 67/548/EEC and following amendments and adjustments. Xi

Danger Symbols:

36/38-43-52/53 R phrases:

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Pictograms:



ΕN



Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 2 / 7

ΕN

	M30	00000F - BCR POLY	SF PARTE A Printed on 21/12/2012 Page n. 2 / 7	
Warning:	Warning			
Hazard indication: H319	Causes serious	eve irritation.		
H315	Causes skin irrit			
H317		llergic skin reaction.		
H412		tic life with long lasting effects.		
Caution recommend				
P264		ighly after handling.		
P273 P280		the environment.	ation / face protection	
P302+P352		gloves / protective clothing / eye protection ash with plenty of soap and water.		
P333+P313		or rash occurs: Get medical advice / atte	ention.	
Contains:	2-idrossietile me	tacrilato		
2.3. Other hazards.				
Information not avai	ilable.			
2 Composition/inf	ormation on in	aradiante		
3. Composition/inf	ormation on ing	greaients.		
3.1. Substances.				
Contains:				
Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).	
2-idrossietile meta	crilato			
CAS. 868-77-9 EC. 212-782-		Xi R36/38, Xi R43, Note D	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Note D	
INDEX. 607-124-	-00-X			
etilvinillbenzene				
CAS. 28106-30	0-1 5-11	Xn R20, Xi R36/37/38, N R51/53	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 2 H411	
EC. 248-846-	-1		Aquatic Chronic 2 H411	
INDEX				
VINILTOLUENE - N	METIL STIRENE -	MIX ISOMERI		
CAS. 25013-15	5-4 5 - 11	R10, Xn R20, Xi R36/37/38	Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319,	
EC. 246-562-	-2		Skin Irrit. 2 H315, STOT SE 3 H335	
INDEX				
T+ = Very Toxic(T+), T = ⁻ Dangerous for the Environ		Xn), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizin	ng(O), E = Explosive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N =	
The full wording of t	he Risk (R) and h	azard (H) phrases is given in section 1	6 of the sheet.	
3.2. Mixtures.				

Information not relevant.

4. First aid measures.

4.1. Description of first aid measures.

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice. SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again. INHALATION: Remove to open air. If breathing is irregular, seek medical advice. INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects caused by the contained substances see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Follow doctor's orders.



Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 3 / 7 ΕN

M300000F - BCR POLY SF PARTE A

5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING MEDIA The extinction equipment should be of the conventional kind: carbon dioxide, foam, powder and nebulised water. EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurised mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event of large quantities of fume.

6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Use breathing equipment if fumes or powders are released into the air.

6.2. Environmental precautions.

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage.

7.1. Precautions for safe handling.

Do not smoke while handling and use.

7.2. Conditions for safe storage, including any incompatibilities.

Store in a well ventilated place, keep far away from sources of heat, bright flames and sparks and other sources of ignition.

Store in a well ventilated place, storage range temperature between 5°C and 30°C. Keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity.

7.3. Specific end use(s).

Information not available.

8. Exposure controls/personal protection.

8.1. Control parameters.

Name	Туре	Country	/ TWA/8h		STEL/15min		
			mg/m3	ppm	mg/m3	ppm	
VINILTOLUENE - METIL STIRENE - MIX ISOMERI							

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product



Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 4 / 7

M3000000F - BCR POLY SF PARTE A

below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitryl or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure. EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an A or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

I			
	Appearance	paste	
	Colour	cream	
	Odour	characteristic	
	Odour threshold.	Not available.	
	pH.	Not available.	
	Melting or freezing point.	Not available.	
	Boiling point.	Not available.	
	Distillation range.	Not available.	
	Flash point.	Not available.	
	Evaporation Rate	Not available.	
	Flammability of solids and gases	Not available.	
	Lower inflammability limit.	Not available.	
	Upper inflammability limit.	Not available.	
	Lower explosive limit.	Not available.	
	Upper explosive limit.	Not available.	
	Vapour pressure.	Not available.	
	Vapour density	Not available.	
	Specific gravity.	1,60 - 1,80	Kg/l
	Solubility	insoluble in water	
	Partition coefficient: n-octanol/water	Not available.	
	Ignition temperature.	Not available.	
	Decomposition temperature.	Not available.	
	Viscosity	Not available.	
	Reactive Properties	Not available.	
	9.2. Other information.		
	VOC (Directive 1999/13/EC) :	5,00 %	
	VOC (volatile carbon) :	4,55 %	
I	· · · · · · · · · · · · · · · · · · ·		

10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

To avoid the exposure on the sunlight.



Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 5 / 7 ΕN

M3000000F - BCR POLY SF PARTE A

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular, however the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

11. Toxicological information.

11.1. Information on toxicological effects.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

12. Ecological information.

This product is dangerous for the environment and the aquatic organisms. In the long term, it may even have negative effects on aquatic environment.

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability.

12.3. Bioaccumulative potential. Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment. Information not available.

12.6. Other adverse effects.

Information not available.

13. Disposal considerations.

Non-hardened material (such as expired or damaged products and/or rejects): e.g. 08 04 09* Glue and sealing materials waste containing organic solvents or other dangerous substances

Hardened material, e.g.: 08 04 10 Glue and sealing materials waste or other dangerous substances, other than classified under 08 04 09.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.



Bossong SpA M3000000F - BCR POLY SF PARTE A

Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 6 / 7 ΕN

15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

None.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product. Point.

Substances in Candidate List (Art. 59 REACH). None.

3

Substances subject to authorisarion (Annex XIV REACH). None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Respiratory / skin sensitization, category 1
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic	2Hazardous to the aquatic environment, chronic toxicity category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R10	FLAMMABLE.
R20	HARMFUL BY INHALATION.
R36/37/38	IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.
R36/38	IRRITATING TO EYES AND SKIN.
R43	MAY CAUSE SENSITIZATION BY SKIN CONTACT.
R51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC
	ENVIRONMENT.
R52/53	HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC
	ENVIRONMENT.

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments

- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament

7. The Merck Index. - 10th Edition

CMSDS EPY 1002



Revision nr.5 Dated 10/12/2012 Printed on 21/12/2012 Page n. 7 / 7

M3000000F - BCR POLY SF PARTE A

8. Handling Chemical Safety

9. Niosh - Registry of Toxic Effects of Chemical Substances

10. INRS - Fiche Toxicologique (toxicological sheet)

11. Patty - Industrial Hygiene and Toxicology

12. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review: The following sections were modified: 01 / 09 / 16.



Revision nr.9 Dated 10/12/2012 Printed on 21/12/2012 Page n. 1/6

ΕN

M2000022F - BCR POLY SF PARTE B

Safety Data Sheet 1. Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier M2000022F Code: Product name **BCR POLY SF PARTE B** Chemical name and synonym Mastic based peroxide 1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use Bi-component injection system for chemical anchor on construction materials 1.3. Details of the supplier of the safety data sheet Name **Bossong SpA** Full address via Enrico Fermi, 51 (BG) District and Country 24050 Grassobbio Italia Tel. 035-3846011 035-3846012 Fax e-mail address of the competent person responsible for the Safety Data Sheet tek@bossong.com 1.4. Emergency telephone number For urgent inquiries refer to Ospedale NIGUARDA Milano tel. +39 0266101029 http://www.centroantiveleni.org/ 2. Hazards identification. 2.1. Classification of the substance or mixture. The product is classified as hazardous pursuant to the provisions set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulationn 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet. 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments. Hazard classification and indication: Eye Irrit. 2 H319 Skin Sens. 1 H317

2.1.2. Directive 67/548/EEC and following amendments and adjustments.

Danger Symbols:	Xi
R phrases:	43

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Pictograms:



Warning:



Bossong SpA M2000022F - BCR POLY SF PARTE B

Revision nr.9 Dated 10/12/2012 Printed on 21/12/2012 Page n. 2 / 6

Hazard indication:			
	iuses serious e ay cause an all	eye irritation. ergic skin reaction.	
Caution recommendatio			
		ghly after handling. gloves / protective clothing / eye protection / face	protection
		sh with plenty of soap and water.	
P333+P313 If s	skin irritation or	r rash occurs: Get medical advice / attention.	
Contains: pe	rossido di dibe	enzoile	
2.3. Other hazards.			
Information not available	9.		
3. Composition/inform	ation on ing	redients.	
3.1. Substances.			
Contains:			
Identification.	Conc. %.	Classification 67/548/EEC.	Classification 1272/2008 (CLP).
perossido di dibenzoil CAS. 94-36-0	e 11 - 20	E R 3, O R 7, Xi R36, Xi R43	Org. Perox B H241, Eye Irrit. 2 H319, Skin Sens. 1 H317
EC. 202-327-6	11-20	, ,	
INDEX. 617-008-00-0			
2-ETILESILBENZOATC CAS. 5444-75-7) 5 - 11	R53	Aquatic Chronic 4 H413
EC. 226-641-8 INDEX.	•		
T+ = Very Toxic(T+), T = Toxic(Dangerous for the Environment((n), C = Corrosive(C), Xi = Irritant(Xi), O = Oxidizing(O), E = Expl	osive(E), F+ = Extremely Flammable(F+), F = Highly Flammable(F), N =
The full wording of the F	Risk (R) and ha	azard (H) phrases is given in section 16 of the she	pet.
3.2. Mixtures.			
Information not relevant			
4. First aid measures.			
4.1. Description of first ai Nevertheless, observan		ustrial hygiene is recommended.	
		ects, both acute and delayed. ibable to the product have been reported.	
4.3. Indication of any imm		al attention and special treatment needed.	
	-		
5. Firefighting measur	es.		
5.1. Extinguishing media. SUITABLE EXTINGUIS			
		f the conventional kind: carbon dioxide, foam, pov	wder and nebulised water.
EXTINGUISHING MEDI None in particular.	A WHICH SH	ALL NOT BE USED FOR SAFETY REASONS	
5.2. Special hazards arisi	na from the c	ubstance or mixture	
HAZARDS CAUSED BY	ÉXPOSURE	IN THE EVENT OF FIRE carbon oxide, toxic pyrolysis products, etc).	
5.3. Advice for firefighters	S.		
GENERAL INFORMATI	ON		
			the development of substances potentially hazardous for ent it from draining into the sewer system. Dispose of
			@ MSDS EPY 1002



Revision nr.9 Dated 10/12/2012 Printed on 21/12/2012 Page n. 3 / 6

M2000022F - BCR POLY SF PARTE B

contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Hardhat with visor, fireproof clothing (fireproof jacket and trousers with straps around arms, legs and waist), work gloves (fireproof, cut proof and dielectric), a depressurised mask with facemask covering the whole of the operator's face or a self-respirator (self-protector) in the event

6. Accidental release measures.

of large quantities of fume.

6.1. Personal precautions, protective equipment and emergency procedures. Use breathing equipment if fumes or powders are released into the air.

6.2. Environmental precautions.

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

6.3. Methods and material for containment and cleaning up.

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage.

7.1. Precautions for safe handling.

Store in closed, labelled containers.

7.2. Conditions for safe storage, including any incompatibilities.

Normal storage conditions without particular incompatibilities.

Store in a well ventilated place, storage range temperature between 5°C and 30°C. Keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, naked flames and sparks and other sources of ignition. Make sure that equipment is available for cooling the vessels, to prevent the danger of overpressure and overheating in the event of fire in the vicinity.

7.3. Specific end use(s).

Information not available.

8. Exposure controls/personal protection.

8.1. Control parameters.

Information not available.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use. Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitryl or equivalent. The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure. EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.



M2000022F - BCR POLY SF PARTE B

Kg/l

Revision nr.9 Dated 10/12/2012 Printed on 21/12/2012 Page n. 4 / 6

9. Physical and chemical properties.

Appearance	paste
Colour	black
Odour	characteristic
Odour threshold.	Not available.
pH.	Not available.
Melting or freezing point.	Not available.
Boiling point.	Not available.
Distillation range.	Not available.
Flash point.	Not available.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Specific gravity.	1,50 - 1,70
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Ignition temperature.	Not available.
Decomposition temperature.	50°C
Viscosity	Not available.
Reactive Properties	Not available.
9.2. Other information.	
VOC (Directive 1999/13/EC) :	0
VOC (volatile carbon) :	0

10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

To avoid the exposure on the sunlight.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid.

None in particular, however the usual precautions used for chemical products should be respected.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

In the event of thermal decomposition or fire, vapours potentially dangerous to health may be released.

11. Toxicological information.

11.1. Information on toxicological effects.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurvies, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scurfy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.



Revision nr.9 Dated 10/12/2012 Printed on 21/12/2012 Page n. 5/6

ΕN

M2000022F - BCR POLY SF PARTE B

12.1. Toxicity.

Information not available.

12.2. Persistence and degradability. Information not available.

12.3. Bioaccumulative potential. Information not available.

12.4. Mobility in soil. Information not available.

12.5. Results of PBT and vPvB assessment. Information not available.

12.6. Other adverse effects.

Information not available.

13. Disposal considerations.

Non-hardened material (such as expired or damaged products and/or rejects): e.g. 08 04 09* Glue and sealing materials waste containing organic solvents or other dangerous substances

Hardened material, e.g.:

08 04 10 Glue and sealing materials waste or other dangerous substances, other than classified under 08 04 09.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

None.

Seveso category.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product. Point.

Substances in Candidate List (Art. 59 REACH). None.

٦

Substances subject to authorisarion (Annex XIV REACH). None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.



Revision nr.9 Dated 10/12/2012 Printed on 21/12/2012 Page n. 6 / 6 ΕN

M2000022F - BCR POLY SF PARTE B

16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Org. Perox BOrganic peroxide, category BEye Irrit. 2Eye irritation, category 2Skin Sens. 1Respiratory / skin sensitization, category 1Aquatic Chronic 4Hazardous to the aquatic environment, chronic toxicity category 4H241Heating may cause a fire or explosion.H319Causes serious eye irritation.H317May cause an allergic skin reaction.H413May cause long lasting harmful effects to aquatic life.

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

R 3	EXTREME RISK OF EXPLOSION BY SHOCK, FRICTION, FIRE OR OTHER SOURCES OF IGNITION.
R 7	MAY CAUSE FIRE.
R36	IRRITATING TO EYES.
R43	MAY CAUSE SENSITIZATION BY SKIN CONTACT.
R53	MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

GENERAL BIBLIOGRAPHY

- 1. Directive 1999/45/EC and following amendments
- 2. Directive 67/548/EEC and following amendments and adjustments
- 3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 6. Regulation (EC) 453/2010 of the European Parliament
- 7. The Merck Index. 10th Edition
- 8. Handling Chemical Safety
- 9. Niosh Registry of Toxic Effects of Chemical Substances
- 10. INRS Fiche Toxicologique (toxicological sheet)
- 11. Patty Industrial Hygiene and Toxicology
- 12. N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review:

The following sections were modified: 16.